



- ① ODN flashing (20°-90°)
- ② VELUX window (GGL 20°-90°)
- ③ VELUX underfelt collar (BFX)
- ④ VELUX insulation frame (BDX)
- ⑤ VELUX vapour barrier (BBX)
- ⑥ VELUX vapour barrier tape (BBX)
- ⑦ Gasket on BBX in window rebate
- ⑧ VELUX Lining (LS-)
- ⑨ Installation batten (Non VELUX)
- ⑩ Trimmer where necessary (Non VELUX)
- ⑪ Felt/breather membrane (Non VELUX)
- ⑫ Ennogie Relief profile (Non VELUX)
- ⑬ Ennogie Side adapter (Non VELUX)
- Gray RAL 7043 Gloss 30
- Black RAL 9005 Gloss 30
- ⑭ Water raiser (Non VELUX)

Roof covering:

Ennogie

VELUX Products:

GGL
20°-90°

ODN
Flashing

Ennogie
Side adapter

BFX

BDX

BBX

LS-

VELUX window sizes:

Size	Width (mm)	Size	Height (mm)
MK--	780	-K08	1398

© VELUX GROUP ® VELUX, VELUX logo are registered trademarks

VELUX			
File name: ENNOGIE-GGL-VAS-804-0118			
Drawing no.:---		SCo: ---	
Create date: 22.01.2018	Rev. date:	Format: A3	Scale: 1:5

Note: When installing VELUX Roof Windows, flashings and installation products, the manufacturers instructions and current building and fire regulations, where applicable, must be met.